



CL SERIES NAVY MAST MOUNT

1,6 - 30 Mhz

GENERAL MECHANICAL FEATURES

Antenna structure:	Epoxy fiberglass
Finishing:	Polyuretanie paint
Colour:	White RAL 9000 (standard) grey RAL 7001 (option)
Irradiation element material:	Brass
Ferrule material:	Chrome plated brass
Chrome plated:	20µm copper, 20µm nikel, 5µm chrome
Working temperature:	-35°C +80°C
Max wind resistance:	150 Km/h

GENERAL ELECTRICAL FEATURES

Frequency:	1,6 - 30 Mhz transmission ATU 0,15 - 30 Mhz reception with transformer
Polarization:	Vertical
Horizontal irradiation:	360°
Connection:	TX with high insulation cable RX with coax cable RG-58 or RG-213
Connecor	8 mm bolt

Code	15752	15652	15552
Model	700 CL NAVY 2P	600 CL NAVY 2P	5,50 NAVY 2P
Length	7,00 mt	6,00 mt	5,50 mt
Electrical Length	6,70 mt	5,70 mt	5,20 mt
Max power	800W	800W	500W
Weight	7 Kg	6Kg	4 Kg
Sections	2	2	2
Bottomn diameter	40mm	40mm	40mm
Length bottomn section - A -	4,00mt	3,50 mt	3,00 mt
Length top section - B -	3,00 mt	2,50 mt	2,50 mt
Base torsion force	150 N	120 N	85N

CL SERIES NAVY MAST MOUNT

1,6 - 30 Mhz

